

## Section 2 Features and Specification



### 2.1 Features and Specifications – Model: 1200

**Unique** - Moving Manifold with ZERO DEGREE Water Jets that deliver HIGH IMPACT Parts washing with “Turbo Shift” High and Low cleaning setting options

Heavy Duty “Hubless” Turntable

Pneumatically controlled Lid for easy operation

Fully Insulated Lid and Body



Zero Degree Water Jet Moving Manifold

**Unique** - Wash Water Treatment Cell - automatically removes oil and dirt and re-injects the detergent back into Parts the Washer

Computer Controlled Electronics with latest water proof membrane control panel

Array of hand cleaning tools – with Hot Water Wash and optional Fresh Water Rinse

service components – “Quick Release” for fast and efficient service and maintenance

Energy Efficient, Safe and Environmentally Responsible

Description	WASHPOD HI 1200
Load capacity	500 kg
Basket size	1200 mm diameter
Internal height	600 mm
Tank capacity	200 L
Pump motor	4.1 kW
Pump water pressure	415 V 3-phase 6.6 A
Pump mechanical seal type	420 Kpa
Wash Water Treatment Cell	Carbon on ceramic
Elements	50 liters
Total electrical load	12.6 A – 3 x 2 kW
Machine weight	17 A
Overall height (lid closed)	495 kg
Clearance height (lid open)	1260 mm
Depth (including lid clearance)	2050 mm
Widths:	1490 mm
	1750 mm